

Drying Ovens Standard Capacity

General Purpose Ovens



Features

9 Sizes 20 to 200 liters
 Temperature range 40 to 250 °C
 Accuracy +/-0.75 °C
 Easy clean powder coated body
 Direct reading thermostat
 Full two year warranty

Options

Stainless steel chamber
 Fan circulation (30 liter +)
 Microprocessor digital or analog controller (fan circulated models)
 Separate LED temperature display
 Horizontal style from 75 liters
 Other accessories available on request

Ref.	Capacity (Liters)	Internal dims. (HxWxD cms)	External dims (HxWxD cms)		No. of Shelves	No. shelf positions	Weight (Kg) aprox.
			Without fan	With fan			
ACT/V20	18	27X27X28	53X39X42	N/A	2	2	16
ACT/V-30	30	24X36X35	50X48X49	50X48X62	2	2	20
ACT/V-40	40	32X36X35	58X45X49	58X45X62	2	3	23
ACT/V-50	50	33X49X33	59X61X47	59X61X59	2	3	26
ACT/V-75	75	33X49X45	59X61X60	59X61X72	2	3	34
ACT/V-100	100	45X49X45	71X61X60	71X61X72	3	4	44
ACT/V-125	125	55X49X45	81X61X60	81X61X72	3	5	52
ACT/V-150	150	55X49X45	81X61X60	81X61X72	3	5	60
ACT/V-200/F	200	75X49X53	N/A	101X61X80	4	7	76

Design

The exterior is constructed from sheet steel finished in easy clean powder coated paint. The interior chamber is made from stainless steel chamber fitted with fixed shelf runners and removable chrome plated wire grid shelves. The top vent is fitted with a clip to hold a mercury-in-glass thermometer.

Some options and accessories means that these ovens can be fully tailored to meet exact requirements